



Product Innovations

Industrial supply

Premium grinding tools since 1919
www.tyrolit.com

TYROLIT

Table of Contents

Cutting	3
Freehand cut-off wheels	3
Grinding wheels	3
Rough grinding wheels	4
Flexible Abrasives	5
Flap discs	6
Belt	7

Symbols



Angle grinder



Mini belt grinder



Stainless steel



Steel



Masonry



Plastics / PVC



Casting materials



Titanium / titanium alloys



Aluminium

Cutting - Freehand cut-off wheels



BASIC CUT-ALL cut-off wheels

for universal use



Application

+ For cutting tasks on a variety of materials

Advantage

+ Universal use on numerous materials

+ Smooth cutting

+ Low burr formation

Form	Type number	Dimension	Specification	PU	
	41	34663835	115 x 1,0 x 22,23	AC 60 Q- BFB	25 Pcs.
		34663836	115 x 1,6 x 22,23	AC 46 Q- BFB	25 Pcs.
		34663838	125 x 1,0 x 22,23	AC 60 Q- BFB	25 Pcs.
		34663840	125 x 1,6 x 22,23	AC 46 Q- BFB	25 Pcs.
		34663882	178 x 1,6 x 22,23	AC 46 Q- BFB	25 Pcs.
		34663883	230 x 1,9 x 22,23	AC 46 Q- BFB	25 Pcs.

Grinding wheels - Rough grinding wheels

★★★ PREMIUM PREMIUM 2in1 CERABOND X COMFORT rough grinding wheels

for steel and stainless steel



Application

- + For demanding applications on various steel and stainless steel qualities, e.g. edge grinding, surface grinding or removal of welding seams

We recommend

- + Developed for increased working comfort and applications with low grinding pressure

Advantage

- + Fast grinding due to the structure of the ceramic grain used
- + Consistent aggressiveness thanks to combination of new bond system with ceramic grain
- + Less pressure required thanks to excellent cutting ability
- + Maximum working comfort over the entire lifetime

Form		Type number	Dimension	Specification	PU
 	27	34645085	178 x 7 x 22,23	CA 24 P- BFP	5 Pcs.
		34611111	230 x 7 x 22,23	CA 24 P- BFP	10 Pcs.

★★★ PREMIUM PREMIUM rough grinding wheels

for cast iron



Application

- + For the most demanding applications on cast iron with lamellar graphite (GJL) and spheroidal cast iron (GJS), for surface grinding as well as for deburring and smoothing work

We recommend

- + Optimised for high-frequency and compressed air-driven turbine angle grinders
- + HARD (S): the deburring specialist offering the longest lifetimes
- + MEDIUM (R): the universal type with increased working comfort
- + SOFT (P): unique comfort and maximum aggressiveness / also suitable for removing cast skin and sandings
- + 4 mm thickness for peripheral grinding (only HARD and MEDIUM) / 7 mm thickness for rough grinding

Advantage

- + Highest stock removal rate thanks to high-quality zirconium aluminium oxide
- + Bond specially adapted to cast iron
- + Edge chipping is reduced to a minimum

Form		Type number	Dimension	Specification	PU
	27	34677713	178 x 4 x 22,23	ZA 24 S- BFP	10 Pcs.
		34675335	178 x 7 x 22,23	ZA24P-BFP	10 Pcs.
		34669681	230 x 4 x 22,23	ZA 24 S- BFP	10 Pcs.
		34675336	230 x 7 x 22,23	ZA24P-BFP	10 Pcs.



PREMIUM VIBSTAR SOFT rough grinding wheels

for cast iron



Application

- + For demanding applications on cast iron and all cast materials, for surface grinding as well as for deburring and smoothing work

Advantage

- + VIBSTAR vibration damping developed and patented by TYROLIT enables especially gentle grinding
- + Multi-layer composition and the permanently attached plastic flange reduce vibrations by up to 50%
- + VIBSTAR technology helps to prevent occupational illnesses such as muscular and skeletal damage, neurological illnesses and circulatory problems

Form	Type number	Dimension	Specification	PU	
	27	34675378	178 x 7 x 22,23	ZA24P-BFP	10 Pcs.
		34675379	230 x 7 x 22,23	ZA24P-BFP	10 Pcs.



STANDARD SIC rough grinding wheels

for cast iron



Application

- + For the removal of cast skin and sandings on cast iron workpieces

Advantage

- + Specially developed for the removal of cast skin and sandings
- + Low grinding pressure needed
- + High aggressiveness
- + Edge chipping is reduced to a minimum

Form		Type number	Dimension	Specification	PU
	27	34675339	178 x 6,5 x 22,23	C24S-BFS	10 Pcs.
		34675338	230 x 6,5 x 22,23	C24S-BFS	10 Pcs.

Flexible Abrasives - Flap discs



BASIC 2in1 flap disc

for steel and stainless steel



Application

- + For grinding applications on different steel and stainless steel grades

We recommend

- + Grit size 40/60 for high stock removal
- + Grit size 80/120 for fine work

Advantage

- + Increased lifetime due to new design with 30% more flaps
- + Good stock removal rate
- + Perfect combination of efficiency and durability

Form	Type number	Dimension	Specification	PU	
 	27A	34656854	115 x 22,23	ZA40-325	10 Pcs.
		34656855	115 x 22,23	ZA60-325	10 Pcs.
		34656856	115 x 22,23	ZA80-325	10 Pcs.
		34656857	115 x 22,23	ZA120-325	10 Pcs.
		34659314	125 x 22,23	ZA40-325	10 Pcs.
		34659315	125 x 22,23	ZA60-325	10 Pcs.
		34659316	125 x 22,23	ZA80-325	10 Pcs.
		34659317	125 x 22,23	ZA120-325	10 Pcs.
		34659318	150 x 22,23	ZA40-325	10 Pcs.
		34659319	150 x 22,23	ZA60-325	10 Pcs.
		34659320	150 x 22,23	ZA80-325	10 Pcs.
		34659341	150 x 22,23	ZA120-325	10 Pcs.
		34659342	178 x 22,23	ZA40-325	10 Pcs.
		34659343	178 x 22,23	ZA60-325	10 Pcs.
		34659344	178 x 22,23	ZA80-325	10 Pcs.
		34659345	178 x 22,23	ZA120-325	10 Pcs.
	28A	34659346	115 x 22,23	ZA40-325	10 Pcs.
		34659347	115 x 22,23	ZA60-325	10 Pcs.
		34659349	115 x 22,23	ZA80-325	10 Pcs.
		34659350	115 x 22,23	ZA120-325	10 Pcs.
		34659371	125 x 22,23	ZA40-325	10 Pcs.
		34659372	125 x 22,23	ZA60-325	10 Pcs.
		34659373	125 x 22,23	ZA80-325	10 Pcs.
		34659374	125 x 22,23	ZA120-325	10 Pcs.
		34659375	178 x 22,23	ZA40-325	10 Pcs.
		34659376	178 x 22,23	ZA60-325	10 Pcs.
		34659377	178 x 22,23	ZA80-325	10 Pcs.
		34659378	178 x 22,23	ZA120-325	10 Pcs.

Flexible Abrasives - Belt



PREMIUM ZA-P47 PE Y mini belts

for steel, stainless steel, titanium and cast iron



Application

- + For universal use on steel, stainless steel, titanium and cast iron with mini belt grinders

We recommend

- + Grit size 40/60 for maximum stock removal
- + Grit size 80/120 for a perfect surface finish

Advantage

- + Zirconium aluminium oxide and an additional coolant layer for maximum lifetime and cool grinding
- + Highest stock removal rates
- + Exceptional aggressiveness and edge stability

Form		Type number	Dimension	Specification	Grain	PU
 	BELT-PE	34648382	9 x 533	ZA-P47	40	20 Pcs.
		34648383	9 x 533	ZA-P47	60	20 Pcs.
		34648384	9 x 533	ZA-P47	80	20 Pcs.
		34648385	9 x 533	ZA-P47	120	20 Pcs.
		34648386	10 x 330	ZA-P47	40	20 Pcs.
		34648387	10 x 330	ZA-P47	60	20 Pcs.
		34648388	10 x 330	ZA-P47	80	20 Pcs.
		34648390	10 x 330	ZA-P47	120	20 Pcs.
		34648402	12 x 520	ZA-P47	40	20 Pcs.
		34648403	12 x 520	ZA-P47	60	20 Pcs.
		34648404	12 x 520	ZA-P47	80	20 Pcs.
		34648405	12 x 520	ZA-P47	120	20 Pcs.
		34648406	13 x 610	ZA-P47	40	20 Pcs.
		34648407	13 x 610	ZA-P47	60	20 Pcs.
		34648408	13 x 610	ZA-P47	80	20 Pcs.
		34648409	13 x 610	ZA-P47	120	20 Pcs.
		34648410	20 x 520	ZA-P47	40	20 Pcs.
		34648411	20 x 520	ZA-P47	60	20 Pcs.
		34648412	20 x 520	ZA-P47	80	20 Pcs.
		34648414	20 x 520	ZA-P47	120	20 Pcs.



Premium CA-P92 PE Y mini belts

for steel, stainless steel and titanium



Application

- + For machining hard steel, stainless steel and titanium with mini belt grinders

We recommend

- + Grit size 40 for maximum stock removal
- + Grit size 60/80 for a perfect surface finish

Advantage

- + Highest possible stock removal thanks to the use of ceramic grain
- + Self-sharpening grain for constantly good surface result combined with reduced operator workload
- + Coolant layer for exceptionally cool grinding

Form	Type number	Dimension	Specification	Grain	PU	
 	BELT-PE	34648416	10 x 330	CA-P92	40	20 Pcs.
		34648417	10 x 330	CA-P92	60	20 Pcs.
		34648418	10 x 330	CA-P92	80	20 Pcs.
		34648419	13 x 457	CA-P92	40	20 Pcs.
		34648420	13 x 457	CA-P92	60	20 Pcs.
		34648421	13 x 457	CA-P92	80	20 Pcs.
		34648423	13 x 610	CA-P92	40	20 Pcs.
		34648424	13 x 610	CA-P92	60	20 Pcs.
		34648425	13 x 610	CA-P92	80	20 Pcs.
		34648426	20 x 520	CA-P92	40	20 Pcs.
		34648427	20 x 520	CA-P92	60	20 Pcs.
		34648428	20 x 520	CA-P92	80	20 Pcs.



PREMIUM ZA-P42 PE Y mini belts

for steel, nonferrous metals and alloys



Application

- + For demanding applications on steel, NF metals and alloys
- + Particularly suitable for wet use

We recommend

- + Grit size 40/60 for maximum stock removal
- + Grit size 80/120 for a perfect surface finish

Advantage

- + Outstanding stock removal rates with light and medium pressure
- + Minimal generation of heat while grinding thanks to active coolant in the bond
- + Longest lifetimes thanks to stiff polyester fabric

Form		Type number	Dimension	Specification	Grain	PU
 	BELT-PE	34648785	9 x 533	ZA-P42	40	20 Pcs.
		34648786	9 x 533	ZA-P42	60	20 Pcs.
		34648788	9 x 533	ZA-P42	80	20 Pcs.
		34648790	9 x 533	ZA-P42	120	20 Pcs.
		34648791	10 x 330	ZA-P42	40	20 Pcs.
		34648792	10 x 330	ZA-P42	60	20 Pcs.
		34648793	10 x 330	ZA-P42	80	20 Pcs.
		34648794	10 x 330	ZA-P42	120	20 Pcs.
		34648796	12 x 520	ZA-P42	40	20 Pcs.
		34648797	12 x 520	ZA-P42	60	20 Pcs.

Form	Type number	Dimension	Specification	Grain	PU
	34648800	12 x 520	ZA-P42	80	20 Pcs.
	34648801	12 x 520	ZA-P42	120	20 Pcs.
	34648802	13 x 610	ZA-P42	40	20 Pcs.
	34648803	13 x 610	ZA-P42	60	20 Pcs.
	34648804	13 x 610	ZA-P42	80	20 Pcs.
	34648805	13 x 610	ZA-P42	120	20 Pcs.
	34648806	20 x 520	ZA-P42	40	20 Pcs.
	34648807	20 x 520	ZA-P42	60	20 Pcs.
	34648808	20 x 520	ZA-P42	80	20 Pcs.
	34648809	20 x 520	ZA-P42	120	20 Pcs.

★ BASIC A-B03 PC X mini belts

for universal use



Application

- + For the machining of various materials, especially steel, stainless steel and NF metals, with portable belt grinders

We recommend

- + Grit size 40/60 for maximum stock removal
- + Grit size 80/120 for a perfect surface finish

Advantage

- + Universally applicable
- + Good lifetime
- + High stock removal with low heat generation
- + Suitable for wet and dry grinding

Form		Type number	Dimension	Specification	Grain	PU
 	BELT-PC	34648279	6 x 610	A-B03	40	20 Pcs.
		34648280	6 x 610	A-B03	60	20 Pcs.
		34648665	6 x 610	A-B03	80	20 Pcs.
		34648666	6 x 610	A-B03	120	20 Pcs.
		34648281	9 x 533	A-B03	40	20 Pcs.
		34648282	9 x 533	A-B03	60	20 Pcs.
		34648667	9 x 533	A-B03	80	20 Pcs.
		34648668	9 x 533	A-B03	120	20 Pcs.
		34648283	10 x 330	A-B03	40	20 Pcs.
		34648284	10 x 330	A-B03	60	20 Pcs.
		34648669	10 x 330	A-B03	80	20 Pcs.
		34648670	10 x 330	A-B03	120	20 Pcs.
		34648285	12 x 520	A-B03	40	20 Pcs.
		34648286	12 x 520	A-B03	60	20 Pcs.
		34648671	12 x 520	A-B03	80	20 Pcs.
		34648673	12 x 520	A-B03	120	20 Pcs.
		34648287	13 x 305	A-B03	40	20 Pcs.
		34648288	13 x 305	A-B03	60	20 Pcs.
		34648675	13 x 305	A-B03	80	20 Pcs.
		34648676	13 x 305	A-B03	120	20 Pcs.
		34648289	13 x 457	A-B03	40	20 Pcs.

Form	Type number	Dimension	Specification	Grain	PU
	34648290	13 x 457	A-B03	60	20 Pcs.
	34648678	13 x 457	A-B03	80	20 Pcs.
	34648679	13 x 457	A-B03	120	20 Pcs.
	34648311	13 x 610	A-B03	40	20 Pcs.
	34648312	13 x 610	A-B03	60	20 Pcs.
	34648681	13 x 610	A-B03	80	20 Pcs.
	34648683	13 x 610	A-B03	120	20 Pcs.
	34648313	20 x 520	A-B03	40	20 Pcs.
	34648314	20 x 520	A-B03	60	20 Pcs.
	34648684	20 x 520	A-B03	80	20 Pcs.
	34648685	20 x 520	A-B03	120	20 Pcs.

TYROLIT-SCHLEIFMITTELWERKE SWAROVSKI AG & CO K.G

Swarovskistraße 33 | 6130 Schwaz | Austria

Tel +43 5242 606-0

Our **worldwide subsidiary** companies can be found
on our website at www.tyrolit.com



Find us on social media
TYROLITgroup